

## SETTING A NEW STANDARD BY WHICH ALL OTHER RIDING GREENSMOWERS WILL BE MEASURED.

The Greensmaster TriFlex and TriFlex Hybrid models are the first riding greens mowers delivering the productivity of a rider and the precision of a walker. Combining the innovative, Double A-Arm Suspension System with industry-leading Flex technology, the cutting units float freely over any terrain resulting in a superior quality of cut and aftercut appearance. And, superior cutting performance is only the beginning. A patented Lift-Gate Footrest and Tool-Free, QuickChange cutting units are just two of the many features that provide added versatility, simplified service, and ultimately, more productivity.

TriFlex Hybrid models feature a reliable all-electric reel circuit that was custom designed with ample power for your most demanding applications, on and off the green. Features that save time and energy, and enhance productivity and turf health combine to make the TriFlex Hybrid the first product to earn the EnergySmart™ label from Toro.



[toro.com/triflex](https://toro.com/triflex)

## FEATURES

### Advanced Cutting Performance

- Patent pending Double A-Arm Suspension for superior contour following.
- Industry leading Flex technology and DPA cutting units for easy adjustment and precision.
- Innovative Lift-In-Turn feature for consistently level cleanup cut.
- Enhanced clippings capture system for improved turf health.

### Highly Productive and Versatile

- Powerful 21 hp (16 kW) Briggs & Stratton®.
- Vanguard Gasoline or 24.8 hp (18 kW) Kubota® diesel engine.
- Ample power for a wide range of applications both on and off the greens.
- 10 mph transport speed to save time and improve productivity.

### Innovative Maintenance Enhancements

- A Lift-Gate Footrest provides easy access to the center cutting unit for simplified maintenance and adjustments.
- Tool-Free, Quick Change cutting units for greater versatility, simplified maintenance, and enhanced productivity.
- Large, balloon-style tires ensure equal pressure on the turf to minimize tire marking and reduce scuffing in turns.

### All-Electric Reel Technology

*(Hybrid models only)*

- Custom designed, highly efficient electrical reel motors.
- Electrical energy storage for peak power demands.
- Sufficient power to verticut.

	GREENSMaster® 3300, TriFlex, MODEL 04510	GREENSMaster® 3320, TriFlex HYBRID, MODEL 04530	GREENSMaster® 3400, TriFlex, MODEL 04520	GREENSMaster® 3420, TriFlex HYBRID, MODEL 04540
ENGINE	Briggs & Stratton® Vanguard®, 21 hp (13.4 kW) @ 3600 rpm, 2-cylinder, air cooled, gasoline engine, governed to 2920 high idle, 1650 rpm low idle. Displacement: 38.3 cu-in (627 cc).		Kubota® D902, Tier 4i, 24.8 hp (18.5 kW) @ 3600 rpm, 3-cylinder, liquid cooled, diesel engine, governed to 2880 high idle, 1560 rpm low idle. Displacement: 55.0 cu-in (902 cc) Radiator: cooled with a 12 volt electric fan.	
FUEL CAPACITY	6 gallons (22.7 liter) capacity.		6 gallons (22.7 liter) capacity. Biodiesel ready up to B20.	
TRACTION DRIVE	2WD parallel hydrostatic or 3WD series-parallel piston pump closed loop system. Foot pedal forward and reverse; infinitely variable.			
GROUND SPEED	Forward-mowing speed is variable from 0-5 mph (0-8 km/h), adjusted by stop on pedal mechanism. Mow speed setting does not affect transport speed. Maximum Greensmaster TriFlex transport speed is 10 mph (16.1 km/h), may be reduced by adjusting stop in footrest pan without affecting mow speeds. Reverse is 3 mph (4.8 km/h) maximum.			
CUTTING UNIT DRIVE	Single gear pump, valve block, series reel drive to 3 reel motors.	48 volt-5400 watt air-cooled brushless permanent magnet generator in parallel with 48 volt 9Ah battery set powers three 48 volt-1100 watt brushless permanent magnet reel motors.	Single gear pump, valve block, series reel drive to 3 reel motors.	48 volt-5400 watt air-cooled brushless permanent magnet generator in parallel with 48 volt 9Ah battery set powers three 48 volt-1100 watt brushless permanent magnet reel motors.
STEERING	Power steering. No tool, quick adjust steering arm position with power assist, with arm motion allowing a wide range of operator sizes. Steering cylinder has a through shaft design for accurate straight line steering.			
ELECTRICAL SYSTEM	12 volt lead acid, group size U1, with 300 minimum cold cranking amps at 0° F and 34 minutes reserve capacity at 85° F/25 amps (29° C/25 amps) draw. 50 amp alternator. Ignition switch/key. Seat switch. Harness terminals and fuse slot available for optional lights installation.		Maintenance-free 12 volt battery with 585 minimum cold cranking amps at 0° F (-17.7° C) and 95 minutes minimum reserve capacity at 85° F (29.4° C) 60 amp alternator, circuit fused at 60 amps. Ignition switch/key. Seat switch. High temperature engine shut down. Harness terminals, fuse slot, and console switch location available for optional lights installation.	
48 VOLT SYSTEM FOR ELECTRIC REELS	NA	4-12 volt 9Ah sealed, maintenance-free, VRLA batteries. 48 volt system is isolated from 12 volt including the frame/chassis.	NA	4-12 volt 9Ah sealed, maintenance-free, VRLA batteries. 48 volt system is isolated from 12 volt including the frame/chassis.
CONTROLS	Ignition: off/run/start; Throttle: low-high Idle; Choke (AC only): open/close choke plate; Parking brake: off/on; Traction pedal: rev/neutral/forward; Joystick: raises/lowers, reels also tap off feature for clean up pass; Functional control lever sets neutral/mow/transport limits for traction pedal; Diagnostic light: indicates system faults to assist in resolving issues (04510 & 04520); InfoCenter™ Diagnostics (04530 & 04540).			
GAUGES	Fuel and hydraulic sight gauges, hour meter. Low oil pressure warning light.	Fuel and hydraulic sight gauges. InfoCenter™: Onboard LCD display shows gauges, alerts/faults, service reminders, electrical system diagnostics, low oil pressure, alternator, engine hours, engine rpm, voltage, functional control status, parking brake applied, reel speed setting, backlap control. <b>New clip selection feature.</b>	Fuel and hydraulic sight gauges, hour meter. Low oil pressure warning light, alternator warning light (on if not charging), glow plug indicator, high engine temperature.	Fuel and hydraulic sight gauges. InfoCenter™: onboard LCD display shows gauges, alerts/faults, service reminders, electrical system diagnostics, low oil pressure, alternator, engine hours, engine rpm, voltage, functional control status, parking brake applied, reel speed setting, backlap control. <b>New clip selection feature.</b>
TIRES/WHEELS/PRESSURE	Three, 19 x 10.5 x 8, 4-ply rating pneumatic tubeless and demountable. Smooth tread. Tire pressure recommended: 12-18 psi front and rear.			
BRAKES	Hand-actuated parking brake lever with two 6" (15.2 cm) diameter drum brakes mounted on the front wheel motors.			
HYDRAULIC OIL	6.8 gallon (25.7 liter) tank.	5.5 gallon (20.8 liter) tank.	6.8 gallon (25.7 liter) tank.	5.5 gallon (20.8 liter) tank.
LEAK DETECTION	Equipped with Turf Guardian™ Leak Detection System. System sounds an alarm and turns on a warning light with the loss of 3-5 ounces of hydraulic oil.	Optional.		
SOUND LEVEL	80 dB(A) at operator's ear under normal conditions.		84 dB(A) at operator's ear under normal conditions.	
OVERALL DIMENSIONS	Wheel Tread: 50.5" (128.3 cm). Wheel Base: 47" (119 cm). Length: 98" (249 cm). Width: 70.62" (179 cm) w/ reels. Height: 80.83" (205 cm).	Wheel Tread: 50.5" (128.3 cm). Wheel Base: 47" (119 cm). Length: 98" (249 cm). Width: 70.84" (180 cm) w/ reels. Height: 80.83" (205 cm).	Wheel Tread: 50.5" (128.3 cm). Wheel Base: 48.6" (123 cm). Length: 98" (249 cm). Width: 70.62" (179 cm) w/ reels. Height: 80.83" (205 cm).	Wheel Tread: 50.5" (128.3 cm). Wheel Base: 48.6" (123 cm). Length: 98" (249 cm). Width: 70.84" (180 cm) w/ reels. Height: 80.83" (205 cm).
WEIGHT	1161 lbs (526 kg).	1257 lbs (570 kg).	1286 lbs (586 kg).	1406 lbs (638 kg).
WIDTH OF CUT	59" (150 cm).			
GROUND CLEARANCE	4.5" (11.4 cm).			
CUTTING UNIT SUSPENSION	Double A-arm suspension utilizing sealed ball joints allows free cutting unit motion in pitch, roll, and yaw. The basket is directly mounted to the cutting unit displacing weight evenly over both cutting unit rollers eliminating the carrier frame, roller and pull links.			
QUICK CONNECT CUTTING UNITS	Quick connect/disconnect feature for both the reel drive motor and cutting unit. No tools required.			
REEL SPEED	Approximately 2050 rpm at 2850 engine rpm. Adjustable.			
BACKLAPPING	Standard equipment.			
OPTIONAL ACCESSORIES	Canopy, verticutters, greens rollers, dethatchers, oil cooler.			
CERTIFICATION	Certified to meet ANSI specification B71.4 - 2004 and European CE standards.			
WARRANTY	Two-year limited warranty. Refer to the Operator's Manual for further details.			

\*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. Consult your local Toro Distributor.

The Greensmaster® TriFlex™ is manufactured in Tomah, WI ISO 9002 Certified Plant.



	8-BLADE DPA CUTTING UNITS, 04651	11-BLADE DPA CUTTING UNITS, 04653	14-BLADE CUTTING UNITS, 04655
DPA CUTTING UNITS	These cutting units will fit on the Greensmaster TriFlex Series.		
HEIGHT OF CUT (HOC) RANGE	Cutting height is adjusted on front roller by two vertical screws and held by two locking cap screws. Bench HOC range is .062"-.297" (.16 cm-.75 cm). With high HOC kit, range is .285-1" (.73 cm-2.54 cm). Effective HOC may vary depending on turf conditions and bedknife installed.		
REEL WELDMENT	Reels are 5" (13 cm) in diameter, 21" (53.3 cm) in length. High carbon steel blades are welded to 5 stamped steel spiders, and heat treated. The reel is ground for diameter and concentricity, and relief grind.		
REEL BEARINGS	Two stainless steel ball bearings, 3.0 cm inside diameter slip fit onto reel shaft retained by internally splined threaded insert. Low drag seals/slingers for added protection with o-ring sealed motor and counterweight. Reel position maintained by a wave washer with no adjusting nut.		
MAINTENANCE	No grease zerks, sealed bearing design eliminates daily maintenance.		
REEL DRIVE	The reel weldment shaft is a 1.375" (3.5 cm) diameter tube with internally splined threaded insert.		
FRAME	Precision machined, die-cast aluminum cross member with two bolt-on die-cast aluminum side plates.		
AGGRESSIVENESS	Aggressiveness stays constant throughout the life of the reel. Patented design.		
BEDKNIFE	Replaceable single edged, EdgeMax™ Microcut Bedknife is standard on all cutting units.		
BEDKNIFE ADJUSTMENT	Dual screw, indexed "click" adjustment to the reel; detents correspond to .0007" (.0018 cm) bedknife movement for each position.		
FRONT & REAR ROLLERS	Front: not included with cutting unit, purchased separately. Option between full, narrow-spaced and wide-spaced Wiehle roller. Rear: steel full, 2" (5.1 cm) diameter with sealed bearings and through-shaft.		
GRASS SHIELD	Non-adjustable shield with adjustable cut-off bar to improve grass discharge from reel in wet conditions.		
TOTAL WEIGHT	8-blade: 80 lbs (30.4 kg) with aluminum Wiehle Roller. 11-blade: 83 lbs (37.7 kg) with aluminum Wiehle Roller. 14-blade: 86 lbs (39 kg) with aluminum Wiehle Roller.		

\*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. Consult your local Toro Distributor.



TRIFLEX TRACTION UNIT ACCESSORIES		TRIFLEX DPA CUTTING UNITS		TRIFLEX DPA CUTTING UNIT ACCESSORIES	
04714	3WD Kit	04651	8-Blade Cutting Unit	04710	Groomer Drive, Forward
04730	Leak Detector	04653	11-Blade Cutting Unit	04260	Groomer Drive, Counter Rotating
04554	Light Kit	04655	14-Blade Cutting Unit	04711	Groomer Reel, Carbide
04718	Seat Kit, Standard	TRIFLEX DPA CUTTING UNIT ROLLERS		04712	Groomer Reel, Spring Steel
04719	Seat Kit, Premium	04625	Full Roller DPA	04713	Groomer Brush, Spiral
92-7307	Armrest Kit - Standard	04626	Narrow Wiehle Roller DPA	04274	Greens Grooming Brush - Soft
119-7105	Armrest Kit - Premium	04627	Wide Wiehle Roller DPA	04275	Greens Grooming Brush - Stiff
119-1691	Hydraulic Oil Cooler Kit (Gas)	04249	Full Split Roller	04724	Rotating Rear Roller Brush - RH
117-9314	Hydraulic Oil Cooler Kit (Diesel)	04250	Wiehle Split Roller	04744	Grooming Reel, Thin Blade (set of 1)
119-7129	2WD Weight Kit (Gas) (ANSI compliant)	04628	Solid Steel Roller Kit (Front Wide Wiehle, Rear Full)	115-1880	EdgeMax™ Microcut Bedknife
121-6665	2WD Weight Kit (Diesel) (ANSI compliant)	04629	Anti Bobbing Roller - DPA (Front and Rear)	115-1881	EdgeMax™ Tournament Bedknife
120-5750	3WD Weight Kit (Gas) (ANSI compliant)	71-1550	2" (5 cm) Rear Wiehle Roller (cast iron)	93-4262	Microcut Bedknife (HOC Range .158 cm - .318 cm)
104-6540	Spark Arrestor Kit (Gas)	125-5180	Rear Roller Extension Kit	93-4263	Tournament Bedknife (HOC Range .32 cm - .635 cm)
120-1951	Spark Arrestor Kit (Diesel)	04258	Extended Wiehle Roller	93-4264	Low Cut Bedknife (HOC Range .635 cm and higher)
115-4510	Canopy	04267	Narrow Wiehle Roller (for paspalum)	94-6392	Bedknife - High Cut
119-1715	Utility Bag Kit	TRIFLEX DPA CUTTING UNIT ROLLERS SCRAPERS/BRUSHES/COMBS		108-4303	Extended Microcut Bedknife
115-4754	Wireless Hour Meter	04646	Rear Roller Scraper (spring loaded)	108-4302	Extended Tournament Bedknife
OPTIONAL TRIFLEX ACCESSORIES		125-3503	Front Wiehle Roller Scraper - Narrow	63-8600	Bedknife - Fairway
04720	Thatching Reel - TriFlex (set of 1)	125-3504	Front Wiehle Roller Scraper - Wide	99-3794-03	DPA Bedbar, Aggressive (optional)
119-1128	Individual dynaBLADE, .2 cm thickness	125-3505	Front Roller Scraper - Full	106-2648-01	DPA Bedbar, Less Aggressive (standard equipment)
117-6824	Individual dynaBLADE, .12 cm thickness	115-7377	Front Wiehle Roller Scraper Brush - Narrow	112-7475	EdgeMax™ Fairway Bedknife
117-6839	Replacement dynaBLADE kit, .12 cm thickness (36 blades)	115-7378	Front Wiehle Roller Scraper Brush - Wide	TRIFLEX SERVICE KITS	
117-6840	Replacement dynaBLADE kit, .2 cm thickness (36 blades)	115-7379	Front Roller Scraper Brush - Full	30042	400 hour filter Maintenance Kit - Greensmaster TriFlex 3300/3320
121-6674	Individual Spring Steel Blade	115-7380	Front Wiehle Roller Scraper Comb - Narrow	30043	400 hour filter Maintenance Kit - Greensmaster TriFlex 3400/3420
121-6675	Replacement Spring Steel Blade Kit (36 pcs)	115-7381	Front Wiehle Roller Scraper Comb - Wide	BIO-HYDRAULIC FLUID/HYDRAULIC FLUID/OIL	
04722	Greens Tri-Roller - TriFlex (set of 1)	115-7382	Front Roller Scraper Comb - Full	119-2157	Bio-Hydraulic Fluid, 5 gal (18.9 L)
04723	Greens Spiker - TriFlex (set of 1)	107-9561	Anti Bobbing Roller - Scraper Kit (front and rear)	119-2158	Bio-Hydraulic Fluid, 55 gal (208.2 L)
		121-2260	Rear Roller Scraper - Adjustable	108-1178	Premium Hydraulic Fluid, 5 gal (18.9 L)
				108-1177	Premium Hydraulic Fluid, 55 gal (208.2 L)
				121-6393	Premium Engine Oil SAE 30, 5 gal (18.9 L)
				121-6392	Premium Engine Oil SAE 30, 55 gal (208.2 L)
				TOOLS	
				04399	Turf Evaluator
				125-5610	Paper - Reel
				125-5611	Shim - Reel
				94-9010	Height of Cut Bar Assembly

\*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. Consult your local Toro Distributor.

The Greensmaster® TriFlex™ is manufactured in Tomah, WI ISO 9002 Certified Plant.



## toro.com

Worldwide Headquarters  
The Toro Company  
8111 Lyndale Ave. So.  
Bloomington, MN 55420 U.S.A.  
Phone: (1) 952 888 8801  
Fax: (1) 952 887 8258

Printed in U.S.A.  
©2016 The Toro Company.  
All Rights Reserved.  
200-7200 GB



facebook.com/ToroCompany  
twitter.com/TheToroCompany  
youtube.com/ToroCompanyEurope



**Count on it.**