



TURF GUARD® WIRELESS SOIL MONITORING SYSTEM



Learn more at
toro.com

Get the essential soil information you need, when you need it. Stay up to date on your current soil conditions no matter where you are. Get the information you need to make important decisions in real time. Turf Guard sensors instantly track soil moisture, salinity, and temperature, saving you time. Repeaters mount easily inside all Toro® Lynx® Smart Satellite pedestals.

Features & Benefits

Reduce Water Usage and Improve Playability

Monitor moisture levels and adjust irrigation without risking turf quality. Promote root growth by avoiding over watering. Detect dry areas before they impact the turf's health.

100% Wireless Network

No wires between the repeaters and the sensors, or the sensor and the probes means that sensors can be installed anywhere on the course without disrupting play. Install sensors without having to trench or pull wires.

Take the Guesswork out of Managing Salinity

Track salt build-up and schedule flushing as needed. Get positive confirmation that your flushing reduced soil salts. Know when and how much water to flush with.



Web-based or Stand-alone Interface

Graphical course overview displays sensor data at-a-glance. Plus with Toro Lynx® Control System integration you can check course moisture, salinity and temperature readings right from your irrigation control software.

TURF GUARD® WIRELESS SOIL MONITORING SYSTEM

How it works:



- Three to five sensors buried in each green at critical root zone levels
- Additional sensors buried in fairways, tee boxes and planters
- Above-ground radio repeaters installed on or in existing irrigation pedestals
- Wireless MESH networking links all sensors to central control system.
- Moisture, Temperature and Salinity readings displayed in your office

SPECIFICATIONS

Operational

- Two distinct depths in the soil profile – critical root zone level and a second 127mm (5") lower. Independent measurements from each depth.
- MESH routing technology offers complete coverage even in remote canyon courses.
- Repeater mounts in most Toro irrigation satellite pedestals. An external repeater is available for other models including non-Toro pedestals.
- Supports up to 500 sensors per course
- Expected sensor battery life of 3 years, field replaceable.
- Sensor reading sent every 5 minutes.
- Automatic network configuration and failure recovery.
- Plots trends and compares historical and current readings.
- Lynx® Control System integration

Electrical

Input Power:

- Repeater: <0,02A @ 6 VAC
- Base Station: <0,1A @ 120 VAC, 50/60 Hz

Sensor dimensions:

- Body: 5,1 cm x 9,2 cm x 15,6 cm (2" x 3.6250" x 6.1250")
- Spikes: 4,4 cm x 0,5 cm (1.7500" x 0.1969")
- Installation Hole Diameter: 10,8cm (4.25")

Sensor temperature:

- Operating: 0°C to 60°C (32°F to 140°F)
- Storage: -30°C to 82°C (-22°F to 180°F)

Sensing:

- 0,1°F Temperature resolution
- 0,1 % Volumetric soil moisture content resolution
- 0,1 dS/m Soil conductivity resolution (Salinity)

Communication:

- Repeater Range: 610m (2000') line-of-sight
- Buried Sensor Range: 152m (500') line-of-sight
- Additional licensing not required

Warranty

- Two years



Specifying Information—Turf Guard

TG-XX-XXX-XX		
Model	Description	Communication
TG	XX-XXX	XX
TG-Turf Guard	S2-R-Sensor, Replaceable Battery B-Base Station R-EXT-Repeater, External R-INT-Repeater, Internal PS-Power Supply	AU-915.5 to 927.5 MHz Band EX-900 MHz ISM Band EU-869 MHz ISM Band

Note: Not available in all locations, please check with your Toro representative for availability.

toro.com

Worldwide Headquarters
The Toro Company
8111 Lyndale Ave. So.
Bloomington, MN 55420 U.S.A.
Phone: (1) 952 888 8801
Fax: (1) 952 887 8258

Printed in U.S.A.
©2016 The Toro Company.
All Rights Reserved.
GB 200-8276NA Electronic file only.



facebook.com
twitter.com/TheToroCompany
youtube.com/ToroCompanyEurope



Count on it.