



Workman® LTX Series

Utility Vehicles

BUILT FOR THIS. POWER MEETS PURPOSE.

The next generation of light-duty utility vehicles is here. The new Workman LTX delivers everything you asked for—power, comfort, and elevated design.

Powered by either the Briggs & Stratton® Vanguard® 400 EFI engine or the Toro HyperCell® lithium battery system, the LTX offers standard height, lifted, or extended models to help you tackle your toughest days. With abundant storage, enhanced options, optimal design, and rugged reliability, you don't have to choose between strength and versatility. The Toro Workman LTX provides both because your work deserves the best.



toro.com

FEATURES

Power Your Way

- Select the Briggs & Stratton® Vanguard® 400 EFI gasoline engine or the advanced Toro HyperCell Lithium-Ion battery system. Both deliver exceptional power, reliability, and efficiency, so you can tackle every job with confidence.

Steering

- An automotive-grade rack and pinion steering system provides more control and lowers steering effort, while operating loaded or empty. This allows operators to focus on the task at hand and nothing else.

Suspension

- Coil-over shocks all around the vehicle deliver greater suspension travel and adjustability resulting in a smoother ride and minimized operator fatigue.

Endless Ways to Customize

- The Workman LTX gives you the flexibility to tackle any job with dozens of configuration options. Choose standard height or lifted models, extend the bed for additional hauling, or add an additional row of seats for more passengers. With accessories to match, you can make your office on wheels your own.

Braking You Can Count On

- Hydraulic disc brakes deliver reliable, consistent stopping power with minimal maintenance, no cable adjustments and less pedal force than traditional mechanical brakes. On lithium-powered models, an electronically controlled parking brake adds an extra layer of convenience.

Intuitive Dashboard Layout

- Oversized cup holders and ample storage for tools and gear. Stay in control with easy-to-reach controls and a clear LCD display. Plus, keep your devices powered on the go with integrated USB-A & C charging ports

ENGINE / POWER SYSTEM	WORKMAN LTX (GAS EFI), MODELS: 07424, 07424LT, 07424EX		WORKMAN LTX (LITHIUM), MODELS: 07425, 07425LT, 07425EX			
ENERGY CAPACITY	408 cc, air-cooled, single cylinder Briggs & Stratton® EFI gasoline engine.		Two HyperCell® lithium-ion batteries standard, option to add an additional battery.			
ELECTRIC MOTOR	N/A		4.32 kWh standard, 6.48 kWh optional. 55 V nominal; 63 V Max			
STEERING	N/A		Brushless high-torque AC Induction motor with 5.0 kW continuous power.			
TURNING RADIUS	Manual rack and pinion steering system with ergonomically positioned column. Steering wheel has 2.75 turns lock-to-lock with 13.75" (35 cm) diameter.		Standard & lifted models: turning clearance circle: 20.7" (6.3 m), inside turning radius: 60.25" (153 cm). Extended models: turning clearance circle: 31' (9.45 m), inside turning radius: 100" (254 cm)			
BRAKES	Front and rear wheel hydraulic disc brakes.					
PARKING BRAKE	Foot pedal with accelerator pedal release.		Automatic parking brake.			
SUSPENSION	Front: modified Macpherson strut. Rear: articulating swing arm. Adjustable coil over shocks at all four wheels.					
SUSPENSION TRAVEL	Front suspension travel: 3.5" (8.9 cm) Rear suspension travel: 4" (10.2 cm).					
FUEL CAPACITY	5 gal (18.9 L)		N/A			
GROUND SPEED	16 mph (25.6 km/h) governed. Speed reduction kits available.		16 mph (25.6 km/h) standard, adjustable up to 24 mph (38.6 km/h). Setting of 19 mph (30.6 km/h) and greater require ROPS & seat belt.			
TRANSAXLE	11.47:1 forward, 14.35:1 reverse					
GROUND CLEARANCE	Standard height models: front: 9" (22.8 cm), rear: 6" (15.2 cm) Lifted models: front: 12" (30.4 cm), rear: 7" (17.8 cm)					
TIRES	Standard & extended models: 20 x 8-10, 4-ply. Or alternate 4-ply/6-ply. Lifted models: 22 x 9.5-12, 4-ply. Or alternate 4-ply/6-ply.					
WHEELS	Standard & extended models: 10" (25.4 cm) steel Lifted models: 12" (30.5 cm) aluminum					
STARTER BATTERY	One 12 V starter battery		N/A			
CONTROLLER	N/A		375 A max with regenerative motor braking, roll-away protection, thermal cutback, sealed/waterproof, status light and three power modes.			
CHARGER	N/A		On-board high efficiency 900 W smart charger. •AC Input Voltage: 100-240 VAC •AC Input Frequency: 50/60 Hz •Max AC Input Current: 13.4 A			
INSTRUMENTS/DASH	LCD display, USB A & C power ports, headlight switch, on/off ignition key switch, horn switch, cup holders, radio holder, and large storage compartments throughout dash.					
STARTING	Pedal or key start capability standard.		Pedal start standard.			
DIMENSIONS	Vehicle Configuration 2-Seat with Bed (Standard Height) 2-Seat with Bed (Lifted) 4-Seat with Bed (Extended) 2-Seat with 6' (1.8 m) Flat Bed (Extended)	Width 47" (119.3 cm) 47" (119.3 cm) 47" (119.3 cm) 47" (119.3 cm)	Length 119" (302 cm) 119" (302 cm) 144" (366 cm) 156" (396 cm)	Height: 50.2" (127 cm) 53.2" (135 cm) 50.2" (127 cm) 50.2" (127 cm)	Wheel Base 77.8" (197 cm) 77.8" (197 cm) 114" (290 cm) 114" (290 cm)	
SEAT	Line installed bolstered bench seat, two-tone gray, with embossed Toro bullhorns on seat backs. Weight: 36 lbs (16 kg).					
CAB DIMENSIONS INSTALLED	Standard height models: height: 79" (201 cm), width: 56" (142 cm) Lifted models: height: 82" (208 cm), width: 56" (142 cm)					
WEIGHT (NOT INCLUDING BED)	2-Seat: 835 lbs (379 kg) 2-Seat Lifted: 860 lbs (390 kg) 2-Seat Extended: 994 lbs (451 kg)		2-Seat: 850 lbs (386 kg) 2-Seat Lifted: 875 lbs (397 kg) 2-Seat Extended: 1,011 lbs (459 kg)			
BEDS	Plastic Cargo Bed: Steel Cargo Bed: 6' (1.8 m) Bed w/Sides:	Width: 37" (94 cm) Width: 43" (109 cm) Width: 46" (117 cm)	Length: 40" (101.6 cm) Length: 44" (111 cm) Length: 72" (183 cm)	Height: 11" (28 cm) Height: 11" (28 cm) Height: 11" (28 cm)	Weight: 122 lbs (55 kg) Weight: 196 lbs (89 kg) Weight: 295 lbs (133 kg)	Capacity: 800 lbs (363 kg) Capacity: 800 lbs (363 kg) Capacity: 800 lbs (363 kg)
CANOPY DIMENSIONS INSTALLED	Standard height models: height: 75.2" (191 cm), width: 54.3" (138 cm) Lifted models: height: 78.2" (199 cm), width: 54.3" (138 cm)					
VEHICLE CAPACITY	2-seat with bed: 1,200 lbs (544 kg)					
TOWING CAPACITY	1,500 lbs (680 kg) Class 1-1.25" receiver standard.					
OPTIONAL ACCESSORIES	Canopy, folding windshield, windshield w/ wiper, seat kit for EX models, steel cargo bed, plastic cargo bed, 6' (1.8 m) flat bed, bed sides, electric bed lift, bed racking, brush guard, brush guard w/ front receiver, trash can mount, ROPS certified cab, cab doors, light options for cab (work lights and beacon), range cage, canopy with ROPS, mirrors, brake/tail/signal lights, back up alarm, under hood storage kit, ram mount ball, 12 V power point kit, all terrain tire kit, telematics kit. Allied accessories: drop-in beverage cart, Kimtek medical bed, Rahn Groomer					
WARRANTY	Two-year or 1,500 hour warranty. Engine warranty with Briggs & Stratton: 3-year commercial warranty +1-year after registering engine at vanguardpower.com/registration . Refer to the Operator's manual for further details.					

* Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. Consult your local Toro Distributor.

Rev. 1/26

2

The Workman LTX is manufactured in Windom, MN ISO 9002 Certified Plant.



toro.com

Worldwide Headquarters
The Toro Company
8111 Lyndale Ave. So.
Bloomington, MN 55420 U.S.A.
Phone: (1) 952 888 8801

©2026 The Toro Company.
All Rights Reserved.
26-209-master



facebook.com
youtube.com/ToroCompanyEurope
x.com/TheToroCompany



Count on it.