

EXCELLENCE IN TURF ROLLING TECHNOLOGY



Lightweight Design, Flawless Results

The HP5.5 Greens Roller offers top performance with its four-roll, ultra-light design minimizing turf compaction for a smooth, uniform surface. Quad-drive oscillating rolls ensure superior traction, eliminating slippage and maintaining consistent rolling across undulating greens.

Designed for efficiency and precision, the HP5.5's articulating roll housings adapt to contours, preventing turf stress. With a 36" rolling swath and 13HP Honda electric start engine, it ensures effortless operation.

Key Features and Benefits:

Lowest PSI in the Lineup - Delivers the lightest ground pressure, reducing turf compaction while maintaining smooth, healthy greens.

Four Driven 5.5" Diameter Rollers - All four rolls are powered, eliminating slippage and ensuring even, consistent rolling for a perfectly uniform playing surface.

Articulating Roll Housings - Independent roll housing ensures full ground contact for smoother, healthier turf.



13 HP Honda Engine

A fuel-efficient, high-output 4-stroke, air-cooled engine with precision camshaft design and high compression ratio for optimal power. Digital CDI ignition to ensure reliable performance.



Drive Rolls

Features four precision-machined rolls, each 5.5 inches in diameter, ensuring optimal ground contact and uniform pressure distribution. All four rolls are driven ensuring superior traction.



Optional Upgrades

LED light kit, Spike-Air Kit, Tournament Roll Kit, Powered Roll Brush, Arm Rest Seat Upgrade, and Pedal Extensions.



Transport Trailer

Features an extra-long tailgate, rubber traction mat, and loading guides for safe transport, along with a swivel jack stand with a caster wheel for easy maneuvering.

HP5.5 GREENS ROLLER



Product Specifications	
Length	45 in (114 cm)
Width	41 in (104 cm)
Height	57 in (145 cm)
Standard Equipment	
Engine	13 HP Honda, Electric Start
Fuel Tank	1.6 Gallons
Controls	On/Off Switch, Choke and Fuel
Battery	12 Volt, 245 CCA automotive type
Hour Meter	Standard
Rolling Swath	36"
Steering Wheel	13-1/4" diameter, automotive type, tilt steering wheel. 13-1 ratio
Drive Rolls	Four (4) - Oscillating steel rolls, driven for positive traction. 5.5" diameter, 36" long with beveled ends. Rolls are machined to within two thousandths of an inch concentrically.
Speed	Variable, 0-11.9 MPH
Brakes	Hydrostatic
Hydraulic Components	Hoses: SAE JIC hose ends & fittings. 3,000 P.S.I. working & 12,000 P.S.I. burst. Motors: Two (2) Char-Lynn 7.3 cubic inch displacement. Pump: One (1) Piston type, .97 cubic inch displacement.
Traction Drive	Hydraulic pump to 2 hydrostats - 1 to each roll. Chain drive from hydraulic motors to rolls. #50 chain & sprockets.
Climbing Traction	Up to 40°
Seat	Molded cushion with protective edge trim, neutral safety switch & forward/reverse adjustment. Rubber mounted to reduce vibration.
Main Frame	2-1/2" x 2-1/2" x 1/4" steel square tube. Fully gusseted with continuous welds.
Trailer Information	
Length	48 in (122 cm)
Width	42 in (107 cm)
Hitch Height	16 in (41 cm)
Weight	197 lb (89 Kg)
Options	
Roller Options	LED Light Kit, Top Dressing Brush Kit: Soft or Hard, Spike-Air Kit, Arm Rest Sea, Pedal Extensions.



ID:187516784665